



SPAR 5 EX AND 5 AXE



PRODUCT FEATURES

- The SPAR 5 EX and 5 AXE are made of Polyspar and can replace rollers of all sizes.
- Its Polyspar ensures optimum sliding without belt wear.
- Recommended for material sizes of 1-1/4" or less.
- Belt speed must be less than 450 fpm.
- Material dropping height must be less than 36".

The SPAR 5 EX and 5 AXE are made for unsafe areas such as transfer points.

Troughing configuration must conform to belt manufacturer recommendations.

Thanks to its good sliding properties, the SPAR 5 EX and 5 AXE will not wear the belt if the belt is clean.

For larger material sizes or material falling from a height greater than 1 m, the SPARET or the SPARMAT are recommended.

GLINDING IDLER

- The SPAR 5 EX and 5 AXE are installed in the place of a roller, thus eliminating the nip point and the risk of nip point accidents.
- Made of Polyspar and designed to replace roller, thanks to their adjustable brackets. No other changes to your belt installation are necessary.



R. BRUNONE

CONTAINMENT • OPTIMISATION • SAFETY OF CONVEYORS

1, rue de la Cressonnière
27950 Saint-Marcel, France
Tél.: +33 (0)2 32 64 20 20
E-mail: commercial.brunone@brunone.fr