



SPARGA

PRODUCT FEATURES



- The **SPARGA** is ideal for **material sizes under 150mm** and **fall height under 2m**.
- Ideal for **belts width from 500 to 1200mm**.
- The **SPARGA** is made of two wear-resistant Polyspar lateral rails mounted on adjustable brackets with choc absorbers.
- The lateral rails make it possible to raise the belt edges to **create a 75° trough**.

THE LEAKPROOF LANDING CRADLE

- The **SPARGA** eliminates the need for **idlers, traditional rubber skirting and skirtboards** at the loading point.
- **Eliminates material leak** at the loading point on belt conveyors.
- The **SPARGA** eliminates **maintenance and fastidious adjustments**.

The **SPARGA** :

- eliminates nip points at loading zones
- improves the belt lifespan
- eliminates rubber skirt adjustments
- improves belt tracking

Thanks to the **SPARGA** mounting system, **adjustments can be made easily, quickly and precisely**.

The belt transition area must be 1,5 to 2 times the belt width according to the belt type and to the conveyor speed



R. BRUNONE

CONTAINMENT • OPTIMISATION • SAFETY OF CONVEYORS

1, rue de la Cressonnière
27950 Saint-Marcel, France
Tél.: +33 (0)2 32 64 20 20

E-mail: commercial@brunone-innovation.fr